

CLAMP-ON CURRENT PROBES			Maximum PRI. (pl) current, A				
Type number	Window diameter	Nominal Z _T Ω	DC to 60 Hz	400 Hz	RF (CW)	Pulse	Frequency range
9124-1N	1.25" (32.0 mm)	0 .001	200	70	50	5000	1 kHz - 200 MHz
9205-1	1.25" (32.0 mm)	0 .33	800	800	50	100	20 Hz - 8 MHz
9118-1	1.25" (32.0 mm)	0 .10	350	150	22	500	500 Hz - 200 MHz
9134-1	1.25" (32.0 mm)	0 .70	500	400	5	100	20 Hz - 100 MHz
6741-1	1.25" (32.0 mm)	0 .70	350	225	5	100	10 kHz - 100 MHz
9207-1	1.25" (32.0 mm)	1 .0	800	450	4 .2	100	20 Hz - 150 MHz
9209-1	1.25" (32.0 mm)	1 .0	800	800	100	200	20 Hz - 30 MHz
9145-1	1.25" (32.0 mm)	5	350	350	42	100	10 kHz - 152 MHz
9123-1N	1.25" (32.0 mm)	1-5	200	200	40	60	10 kHz - 500 MHz
9214-1	1.25" (32.0 mm)	5	600	600	21	200	20 Hz - 150 MHz
9215-1N	1.25" (32.0 mm)	1-5	400	350	40	100	20 Hz - 500 MHz
9231-1	1.25" (32.0 mm)	.010	300	200	7	3000	1 kHz - 200 MHz
9219-1N	1.25" (32.0 mm)	.025	400	300	150	200	20 Hz - 20 MHz
9250-1N	1.25" (32.0 mm)	.10	200	200	10	200	10 kHz - 450 MHz
9257-1N	2.62" (67.0 mm)	4	500	500	200	200	20 Hz - 30 MHz
9258-1N	2.62" (67.0 mm)	5	500	500	100	200	20 Hz - 100 MHz
9261-1N	2.62" (67.0 mm)	2	500	500	2 .6	100	20 Hz - 200 MHz
9263-1N	2.62" (67.0 mm)	.03	500	500	80	200	20 Hz - 100 MHz
9301-1N	2.62" (67.0 mm)	8	350	350	60	200	20 Hz - 500 MHz
9303-1N	2.62" (67.0 mm)	.001	500	200	100	5000	20 Hz - 100 MHz
9305-1N	2.62" (67.0 mm)	1	500	500	2 .3	200	20 Hz - 200 MHz
9306-1N	2.62" (67.0 mm)	.005	800	300	14	5000	1 kHz - 100 MHz
9307-1N	2.62" (67.0 mm)	.005	300	300	60	5000	20 Hz - 100 MHz
21406-1N	2.62" (67.0 mm)	.01	350	350	40	2200	100 Hz - 30 MHz